



- 1) Connect two fully charged battery packs to the EVX-2 electronic speed control (ESC) and turn on your transmitter. 2) The EZ-SET® button on the EVX-2 turns the model on and off.
- Press the EZ-SET button until the light turns green and then release. The light MUST be on for proper operation. If the light is not green, the speed control is not fully on. 3) For forward throttle, pull the throttle trigger on the transmitter
- towards you.
- 4) For braking, push the throttle trigger forward (away from you). As the model is rolling, the brakes can be applied multiple times.
- 5) For reverse, come to a complete stop and push the throttle trigger forward.
- 6) To turn the model (ESC) off, press the EZ-SET button until the green light turns off.

- If the model will be off for more than a few minutes. disconnect the battery.
- 8) Always disconnect and remove batteries for storage.
- EVX-2 Operating Modes (Profiles): Changing the mode is done by pressing and holding the EZ-SET button until the EVX-2 blinks red the number of times that correspond with the desired Mode. Release the FZ-SFT button to select the Mode.
 - 1) Connect a fully charged battery pack to the EVX-2 and turn on your transmitter.
- 2) With the EVX-2 off, press and hold the set button until the light turns solid green, then solid red (indicating programming mode), and then begins blinking red (indicating the Mode numbers).

- 3) The light will blink once (Profile 1, Standard Mode), then twice (Profile 2, Race Mode), and then 3 times (Profile 3, Training Mode™). If you missed the mode you wanted, keep the EZ-SET button pressed down and the blink cycle will repeat until a Mode is selected
- 4) Release the set button after the light blinks the Mode number you wish to select.
- The light will then turn green and the model is Ready-To-Drive?

Tip For Fast Mode Changes: The EVX-2 is set to Profile 1 Standard Mode as the default. To quickly change to Profile 3 Training Mode, with the transmitter on, press and hold the EZ-SET button until the light blinks red 3 times and then release.

To quickly change back to Profile 1 Standard Mode (full power). with the transmitter on and the EVX-2 off, press and hold the EZ-SET button until the light turns green, red, shuts off, blinks red one time and then release

Caring for Your Motor: Your model is equipped with dual Titan® 550 motors. Follow these tips to maintain the best performance and longest life. 1) Break in the motors by driving smoothly for the first pair

- of battery packs. This will allow the brushes to seat. 2) Avoid abusive driving that puts extreme current loads on the motors causing them to become hot. Examples include driving through deep sand, tall grass, attempting to push immovable
- objects, and repetitive starting, stopping, and direction changes. 3) The EVX-2 is equipped with thermal shutdown protection to protect its circuitry, but it does not protect the motors from
- thermal damage caused by abusive driving.