

# X-Maxx (Model 77086-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

|  | Bearings & Bushings   | 7790   | Pinion gear, differential, 11-tooth (front) (heavy duty) (use with #7792 35-tooth differential ring gear)  |
|--|---|--|--|
| 5106A<br>5108A                                 | Ball bearing, black rubber sealed (15x24x5mm) (2)<br>Ball bearing, black rubber sealed (15x26x5mm) (2)  | 7791   | Pinion gear, differential, 11-tooth (rear) (heavy duty) (use with #7792  |
| 5107A  | Ball bearing, black rubber sealed (17x26x5mm) (2)   | 7700   | 35-tooth differential ring gear)   |
| 5182A  | Ball bearing, black rubber sealed (20x27x4mm) (2)   | 7792   | Ring gear, differential, 35-tooth (heavy duty) (use with #7790, #7791 11-tooth differential pinion gears)  |
| 5106   | Ball bearing, blue rubber sealed (15x24x5mm) (2)  | 7783   | Spider gear shaft (2)/ spacers (4)/ 16x23.5x.5mm TW (2)  |
| 4611   | Ball bearings (5x11x4mm) (2)  | 7783X  | Spider gear shaft (2)/ spacers (4)/16x23.5x.5 stainless washer (2) (for  |
| 5120A  | Ball bearings, black rubber sealed (12x18x4mm) (2)  |  | #7781X aluminum differential carrier)  |
| 5180A  | Ball bearings, black rubber sealed (6x13x5mm) (2)   |  | Driveline Components   |
| 5119<br>5116                                   | Ball bearings, blue rubber sealed (10x15x4mm) (2)<br>Ball bearings, blue rubber sealed (5x11x4mm) (2)   | 7752   | Carriers, stub axle (left & right)   |
| 5110   |   | 7794   | Cush drive key/ pin/ elastomer damper  |
|  | Body & Accessories  | 7754X  | Drive cup (1)/ 3x8mm CS (use only with #7750X driveshaft)  |
| 7715   | Body mounts, front & rear/3x15mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head machine screw (2)   | 7755<br>7750X  | Driveshaft assembly, center, aluminum<br>Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1)   |
| 7713   | Body support, rear/ 3x15mm CS (2) / 3x15mm flat-head machine (2) (fits X-Maxx®)   | 5040   | (replacing #7750 also requires #7751X, #7754X and #7768, #7768R, or #7768G)<br>Oil, differential (20M weight) (standard)   |
| 7711   | Body, X-Maxx® (clear, trimmed, requires painting)/ window   | 7751X  | Rebuild kit, steel constant-velocity driveshaft (includes pins for 2   |
| 7711A  | masks/ decal sheet<br>Body, X-Maxx®, blue (painted, decals applied) (assembled with front   | 7768A  | driveshaft assemblies (use only with #7750X driveshaft)<br>Stub axle, aluminum (black-anodized) (1) (use only with #7750X  |
| 7711G  | & rear body mounts, rear body support, and tailgate protector)<br>Body, X-Maxx®, green (painted, decals applied) (assembled with  | 7768   | driveshaft)<br>Stub axle, aluminum (blue-anodized) (1) (use only with #7750X   |
|  | front & rear body mounts, rear body support, and tailgate protector)  |  | driveshaft)  |
| 7711X  | Body, X-Maxx®, ProGraphix® (graphics are printed, requires<br>paint & final color application)/ decal sheet   | 7768G  | Stub axle, aluminum (green-anodized) (1) (use only with #7750X driveshaft)   |
| 7711R  | Body, X-Maxx®, red (painted, decals applied) (assembled with front & rear body mounts, rear body support, and tailgate protector)   | 7768R  | Stub axle, aluminum (red-anodized) (1) (use only with #7750X driveshaft)   |
| 7711T  | Body, X-Maxx®, Rock n' Roll (painted, decals applied)   | 7758A  | Wheel nuts, splined, 17mm, serrated (black-anodized) (4)   |
| 7740   | (assembled with tailgate protector)   | 7758   | Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)  |
| 7712   | Tailgate protector/ 3x8mm flat-head screw (4)   | 7758G  | Wheel nuts, splined, 17mm, serrated (green-anodized) (4)   |
|  | Bumpers & Skidplates  | 7758R  | Wheel nuts, splined, 17mm, serrated (red-anodized) (4)   |
| 7733   | Bumper mount, front/ bumper support   |  | Front Suspension & Steering  |
| 7734   | Bumper mount, rear/ bumper support  | 7726   | Bulkhead tie bar, upper (1)/ lower (2) (steel)   |
| 7735   | Bumper, front   | 7721   | Bulkhead, front (lower)  |
| 7736<br>7745                                   | Bumper, rear<br>Skidplate, center   | 7720   | Bulkhead, front (upper)  |
| 7744   | Skidplate, front (1), rear (1)/ rubber impact cushion (2)   | 7752<br>7732   | Carriers, stub axle (left & right)<br>Caster blocks (c-hubs), left & right   |
|  | Chassis & Attachments   | 7716   | Mount, tie bar, front (1)/ rear (1)  |
| 7719   |   | 7747   | Servo horn, steering/ linkage, steering (46mm, assembled with pivot  |
| 7718   | Battery hold-down (2)/ foam pad (2)<br>Battery hold-down mounts, left (2)/ right (2)/ 3x18mm CS (4)   |  | balls)   |
| 7715   | Body mounts, front & rear/3x15mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head machine   | 7739<br>7746   | Shock tower, front (left & right halves)<br>Steering bellcranks/ bellcrank support/servo saver/ servo saver  |
|  | screw (2)   | 7707   | spring/ draglink/ 3x20mm shoulder screws (2)   |
| 7724   | Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ $3x15$ CS (4)   | 7737<br><b>7746X</b>                                 | Steering blocks, left & right<br>Steering link, steel/ servo saver spring, heavy duty (use with<br>#2085X metal gear servo)  |
| 7733   | Bumper mount, front/ bumper support   | 7731   | Suspension arms, lower (left, front or rear) (1)   |
| 7734   | Bumper mount, rear/ bumper support  | 7730   | Suspension arms, lower (right, front or rear) (1)  |
| 7735<br>7736                                   | Bumper, front<br>Bumper, rear   | 7729   | Suspension arms, upper (left or right, front or rear) (2)  |
| 7722   | Chassis   | 7743   | Suspension pin retainer (4)  |
| 7714X  | Chassis top brace   | 7740   | Suspension pin set, front or rear corner (hardened steel), 4x85mm  |
| 7723   | Nerf bars, chassis (2)  | 7740   | (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)   |
| 7725   | Seal kit, receiver box (includes o-ring, seals, and silicone grease)  | 7742   | Suspension pin set, shock mount (front or rear, hardened steel),<br>4x25mm (2), 4x38mm (2)   |
| 7745   | Skidplate, center   | 7741   | Suspension pins, 4x85mm (hardened steel) (2)   |
| 7744   | Skidplate, front (1), rear (1)/ rubber impact cushion (2)   |  | Hardware   |
| 7717X<br>7776                                  | Spacer, battery compartment (2)/ foam blocks (4)/ foam pad (2)<br>Wheelie bar, black (assembled)  | 2585   | Cylinder head bolts, marine 3x20mm CS (6) (TRX 2.5)  |
| 7775   | Wheels (2) (for #7776 wheelie bar)  | 2584   | Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5, 2.5R, 3.3)  |
|  | Cush Drive Components   | 2586   | Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5)   |
| 7794   | Cush drive key/ pin/ elastomer damper   | 4955   | Pins, axle (2.5x12mm) (4)  |
| 7793X  | Housing, cush drive (front & rear halves)   | 3234   | Screws, 2.5x14mm cap-head machine (hex drive) (6)  |
| 6447X  | Spur gear, 46-tooth, steel (1.0 metric pitch)<br>Spur gear, 50-tooth, steel (1.0 metric pitch)  | 2577   | Screws, 3x10mm button-head machine (hex drive) (6)   |
| 6448¥  | epar your, vo-tooth, stoer (1.0 metho pitch)  | 2587   | Screws, 3x10mm cap-head machine (6) (no washer)  |
| <b>6448X</b><br>6449X                          | Spur gear, 54-tooth, steel (1.0 metric pitch)   |  | Screws, 3x10mm flat-head machine (hex drive) (4)   |
| <b>6448X</b><br>6449X                          | Spur gear, 54-tooth, steel (1.0 metric pitch)   | 4859   |  |
| 6449X  | Differential Components   | 2593   | Screws, 3x14mm button-head machine (hex drive) (6)   |
| 6449X<br>7781X                                 | Differential Components<br>Carrier, differential (aluminum) (requires #7783X spider gear shaft)   | 2593<br>2579   | Screws, 3x14mm button-head machine (hex drive) (6)<br>Screws, 3x15mm button-head machine (hex drive) (6)   |
| 6449X<br>7781X<br>7781                         | Differential Components<br>Carrier, differential (aluminum) (requires #7783X spider gear shaft)<br>Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW   | 2593<br>2579<br>3646                                 | Screws, 3x14mm button-head machine (hex drive) (6)<br>Screws, 3x15mm button-head machine (hex drive) (6)<br>Screws, 3x15mm flat-head machine (hex drive) (6)   |
| 6449X<br>7781X<br>7781<br><b>5136X</b>         | Carrier, differential (aluminum) (requires #7783X spider gear shaft)<br>Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW<br>Differential oil kit (1 each: 10K, 30K, 50K weights)  | 2593<br>2579   | Screws, 3x14mm button-head machine (hex drive) (6)<br>Screws, 3x15mm button-head machine (hex drive) (6)   |
| 6449X<br>7781X<br>7781                         | Differential Components<br>Carrier, differential (aluminum) (requires #7783X spider gear shaft)<br>Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW   | 2593<br>2579<br>3646<br>4857<br>2581<br>2575         | Screws, 3x14mm button-head machine (hex drive) (6)<br>Screws, 3x15mm button-head machine (hex drive) (6)<br>Screws, 3x15mm flat-head machine (hex drive) (6)<br>Screws, 3x20mm countersunk machine (hex drive) (6)   |
| 6449X<br>7781X<br>7781<br><b>5136X</b>         | Differential (aluminum) (requires #7783X spider gear shaft)<br>Carrier, differential (aluminum) (requires #7783X spider gear shaft)<br>Carrier, differential/x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW<br>Differential oil kit (1 each: 10K, 30K, 50K weights)<br>Gear set, differential (output gears (2)/ spider gears (4)/                         | 2593<br>2579<br>3646<br>4857<br>2581<br>2575<br>2576 | Screws, 3x14mm button-head machine (hex drive) (6)<br>Screws, 3x15mm button-head machine (hex drive) (6)<br>Screws, 3x15mm flat-head machine (hex drive) (6)<br>Screws, 3x20mm countersunk machine (hex drive) (6)<br>Screws, 3x25mm button-head machine (hex drive) (6)<br>Screws, 3x6mm button-head machine (hex drive) (6)<br>Screws, 3x8mm button-head machine (hex drive) (6) |
| 6449X<br>7781X<br>7781<br><b>5136X</b><br>7782 | Differential (aluminum) (requires #7783X spider gear shaft)<br>Carrier, differential (aluminum) (requires #7783X spider gear shaft)<br>Carrier, differential/x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW<br>Differential oil kit (1 each: 10K, 30K, 50K weights)<br>Gear set, differential (output gears (2)/ spider gears (4)/<br>16x23.5x.5mm TW (2)) | 2593<br>2579<br>3646<br>4857<br>2581<br>2575         | Screws, 3x14mm button-head machine (hex drive) (6)<br>Screws, 3x15mm button-head machine (hex drive) (6)<br>Screws, 3x15mm flat-head machine (hex drive) (6)<br>Screws, 3x20mm countersunk machine (hex drive) (6)<br>Screws, 3x25mm button-head machine (hex drive) (6)<br>Screws, 3x6mm button-head machine (hex drive) (6)  |

### Page 2 X-Maxx: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 77086-4) Parts List

| 3938  | Screws, 4x14mm button-head machine (hex drive) (6) |
|-------|--|
| 2594  | Screws, 4x15mm button-head machine (hex drive) (6) |
| 2546  | Screws, 4x15mm countersunk machine (hex drive) (6) |
| 3933  | Screws, 4x16mm button-head machine (hex drive) (6) |
| 2597  | Screws, 4x22mm button-head machine (hex drive) (6) |
| 2596  | Screws, 4x25mm button-head machine (hex drive) (6) |
| 2598X | Screws, 4x30mm button-head machine (hex drive) (6) |
| 2595  | Screws, 4x35mm button-head machine (hex drive) (6) |
| 2743  | Set (grub) screws, 3mm hardened (12)               |
| 3642X | Shoulder screws, Ultra Shocks (3x12 hex drive) (6) |
|       | IFN Linkto   |

## LED Lights

7885 LED light kit, complete (includes #6590 high-voltage power amplifier)

## tors & Electronics

|                | Motors & Electronics   |
|----------------|--|
| 7749           | Adapter, standard servo (adapts standard servo to fit in X-  |
| 3475           | Maxx®)<br>Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)  |
| 7787           | Covers, gear (3)   |
| 3474           | Dual cooling fan kit (with shroud), Velineon® 1200XL motor   |
| 2087           | Gear set (for 2085 servo)  |
| 2087<br>2087X  | Gear set, metal (for 2005 & 2085X servos)  |
| 3362           | Heat sink, Velineon® 1600XL  |
| 7760           | Motor mounts (front and rear)/ pins (2)  |
| 3491           | Motor, Velineon® 1200XL, brushless   |
| 2086           | Servo case/gaskets (for 2085 servo)  |
| 2080           | Servo, digital high-torque (ball bearing), waterproof (X-Maxx® mount)  |
| 2085<br>2085X  | Servo, digital high-torque, metal gear (ball bearing), waterproof (x-maxwe mount)                                      |
|                | servo saver spring/ steering link  |
| 3496           | Velineon® VXL-8s Electronic Speed Control, waterproof (brushless)<br>(fwd/rev/brake)                                   |
| 7759           | Washers, motor mount, aluminum (blue-anodized) (4)/ 4x18mm<br>BCS (4)  |
| 7759G          | Washers, motor mount, aluminum (green-anodized) (4)/ 4x18mm<br>BCS (4)   |
| 7759R          | Washers, motor mount, aluminum (red-anodized) (4)/ 4x18mm  |
|                | BCS (4)<br>Radio Suotom Rottovico o Oboverovo  |
|                | Radio System, Batteries & Chargers   |
| 2854X          | 10000mAh 7.4v 2-Cell 25C LiPo Battery  |
| 2872X          | 5000mAh 11.1v 3-Cell 25C LiPo Battery  |
| 2888X          | 5000mAh 14.8v 4-Cell 25C LiPo Battery  |
| 2889X          | 5000mAh 14.8v 4-Cell 25C LiPo Battery  |
| 2857X          | 6400mAh 11.1v 3-Cell 25C LiPo Battery  |
| 2890X          | 6700mAh 14.8v 4-Cell 25C LiPo Battery  |
| 2878X          | 8400mAh 11.1v 3-Cell 25C LiPo Battery  |
| 2938X          | Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries to separate balance ports)                             |
| 2943           | Battery charge indicators (green (4), blue (4), grey (4))  |
| 6548           | Battery door, transmitter (replacement for #6516, 6517, 6528, 6529, 6530 transmitters)                                 |
| 2914           | Battery, Power Cell AA Alkaline (4)  |
| 2993           | Battery/charger completer pack (includes #2971 iD® charger (1),<br>#2890X 6700mAh 14.8V 4-cell 25C LiPo battery (2))   |
| 2990           | Battery/charger completer pack (includes #2972 Dual iD® charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2)) |
| 2972           | Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery Identification   |
| 2973           | Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto   |
| 2971           | Battery Identification<br>Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery                                |
|                | Identification   |
| 2970           | Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto<br>Battery Identification                                       |
| 6525           | Communication link, telemetry expander   |
| 2087           | Gear set (for 2085 servo)  |
| 2087X<br>2968X | Gear set, metal (for 2085 & 2085X servos)<br>LiPo cell voltage checker/balancer (includes #2938X adapter for           |
| 2968           | Traxxas® iD® batteries)<br>LiPo cell voltage checker/balancer (requires #2938X adapter for                             |
|                | Traxxas® iD® batteries)  |
| 6533<br>6552   | Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)   |
| 6552           | Seal kit, expander box (includes o-ring, seals, and silicone grease)   |
| 6526           | Sensor, auto-detectable, temperature   |
| 6527           | Sensor, auto-detectable, voltage   |
| 6531           | Sensor, temperature & voltage (fits X-Maxx®)   |
| 6521           | Sensor, temperature and voltage (long)   |
| 2086           | Servo case/gaskets (for 2085 servo)  |
| 2085           | Servo, digital high-torque (ball bearing), waterproof (X-Maxx® mount)  |
| 2085X          | Servo, digital high-torque, metal gear (ball bearing), waterproof/<br>servo saver spring/ steering link                |

| 6553X  |  |
|--|--|
|  | Telemetry expander 2.0 and GPS module 2.0, TQi radio system  |
| 6550X  | Telemetry expander 2.0, TQi radio system (compatible only with   |
|  | #6551X GPS module)   |
| 6550   | Telemetry expander, TQi radio system   |
| 6551X  | Telemetry GPS module 2.0, TQi radio system (compatible only  |
| 0551X  | with #6550X telemetry expander)  |
| 6509R  | TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™   |
| 03091  | enabled, TSM (2-ch transmitter, 5-ch micro receiver)   |
| 6507R  | TQi 2.4 GHz High Output radio system, 4-channel with Traxxas   |
| 000710   | Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro   |
|  | receiver)  |
| 6528   | Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-   |
| 0020   | channel (transmitter only)   |
| 6529   | Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-   |
|  | channel (transmitter only)   |
| 6530   | Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-   |
|  | channel (transmitter only)   |
| 6511   | Traxxas Link™ Wireless Module  |
|  | Ready-To-Race Model  |
|  |  |
| 77086-4  | X-Maxx®: Brushless Electric Monster Truck with TQi Traxxas Link™   |
|  | Enabled 2.4GHz Radio System & Traxxas Stability Management   |
|  | (TSM)®   |
|  | Rear Suspension  |
| 7726   | Bulkhead tie bar, upper (1)/ lower (2) (steel)   |
| 7727X  | Bulkhead, rear (upper & lower), center differential (replacing #7727 &   |
|  | #7728 requires #5107A ball bearings (2))   |
| 7752   | Carriers, stub axle (left & right)   |
| 7716   | Mount, tie bar, front (1)/ rear (1)  |
| 7738   | Shock tower, rear (left & right halves)  |
| 7731   | Suspension arms, lower (left, front or rear) (1)   |
| 7730   | Suspension arms, lower (right, front or rear) (1)  |
| 7729   | Suspension arms, upper (left or right, front or rear) (2)  |
| 7743   | Suspension pin retainer (4)  |
| 7740   | Suspension pin set, front or rear corner (hardened steel), 4x85mm  |
|  | (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)   |
| 7742   | Suspension pin set, shock mount (front or rear, hardened steel),   |
|  | 4x25mm (2), 4x38mm (2)   |
| 7741   | Suspension pins, 4x85mm (hardened steel) (2)   |
|  | Shocks (GTX)   |
| 7765 4   |  |
| <b>7765A</b><br>7765   | Body, GTX shock (aluminum, black-anodized) (1)   |
| 7765G  | Body, GTX shock (aluminum, blue-anodized) (1)  |
|  | Body, GTX shock (aluminum, green-anodized) (1)   |
| 7765R  | Body, GTX shock (aluminum, red-anodized) (1)   |
| 7765X  | Body, GTX shock (hard-anodized, PTFE-coated aluminum) (1)<br>Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston  |
| 7762   | nuts, bladders) (renews 2 shocks)  |
| 7763   | Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls)   |
| 1105   | Shart, GTA shock, Tronnin (assembled with rod ends & hollow balls)   |
|  | (steel chrome finish) (2)  |
| 7762T  | (steel, chrome finish) (2)   |
| 7763T  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and  |
|  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls)  |
| 7763T<br>7764A   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers   |
| 7764A  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)   |
|  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/   |
| 7764A<br>7764G   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)  |
| 7764A  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX  |
| 7764A<br>7764G   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)  |
| 7764A<br>7764G<br>7764X  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)   |
| 7764A<br>7764G<br>7764X  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers   |
| 7764A<br>7764G<br>7764X<br>7764R   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)  |
| 7764A<br>7764G<br>7764X<br>7764R   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o   |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)   |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)   |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761<br>7761A<br>7761G   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761R  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)   |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667   | <ul> <li>Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls)</li> <li>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2) (for 2 shocks)</li> <li>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> </ul>  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761R  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)   |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667<br>7767   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667   | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667<br>7767<br>7767G  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks (4) (assembled with o-ring)  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667<br>7767   | <ul> <li>Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and steel hollow balls)</li> <li>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, aluminum (green-anodized), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8)</li> <li>Shock caps, aluminum (black-anodized), GTX shocks (4)/ spacers (8)</li> <li>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs) (2)</li> <li>Shicone shock oil (30 wt), 60cc</li> <li>Spring retainer (adjuster), blue-anodized aluminum, GTX shocks (4) (assembled with o-ring)</li> <li>Spring retainer (adjuster), green-anodized aluminum, GTX shocks (4) (assembled with o-ring)</li> <li>Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks</li> </ul>  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667<br>7767<br>7767G<br>7767G<br>7767X                          | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully as |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667<br>7767<br>7767G  | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks (4) (assembled with o-ring)<br>Spring retainer (adjuster), blue-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), red-anodized aluminum, GTX shocks   |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761R<br>1667<br>7767<br>7767G<br>7767G<br>7767X<br>7767R                          | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks (4) (assembled with o-ring)<br>Spring retainer (adjuster), blue-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)  |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667<br>7767<br>7767G<br>7767G<br>7767X<br>7767R<br>7853         | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum, (red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Springs, shock (natural finish) (GTX) (0.824 rate) (2)   |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667<br>7767<br>7767G<br>7767X<br>7767R<br>7767R<br>7853<br>7854 | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), GTX (0.824 rate) (2)<br>Springs, shock (natural finish) (GTX) (0.824 rate) (2)   |
| 7764A<br>7764G<br>7764X<br>7764R<br>7764<br>7761A<br>7761G<br>7761G<br>7761R<br>1667<br>7767<br>7767G<br>7767G<br>7767X<br>7767R<br>7853         | Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and<br>steel hollow balls)<br>Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, aluminum (green-anodized), GTX shocks (4)/<br>spacers (8)<br>Shock caps, aluminum (hard-anodized, PTFE-coated), GTX<br>shocks (4)/ spacers (8)<br>Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers<br>(8)<br>Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)<br>(for 2 shocks)<br>Shocks, GTX, aluminum (black-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (green-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum (red-anodized) (fully assembled w/o<br>springs) (2)<br>Shocks, GTX, aluminum, (red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), PTE-coated aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), forta-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Spring retainer (adjuster), red-anodized aluminum, GTX shocks<br>(4) (assembled with o-ring)<br>Springs, shock (natural finish) (GTX) (0.824 rate) (2)   |

### Page 3 X-Maxx: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 77086-4) Parts List

| Page 3              | X-Maxx: TQi Traxxas Link Enabled 2.4GHz Radio &   |
|---------------------|---|
| 7856                | Springs, shock (natural finish) (GTX) (1.346 rate) (2)  |
| 7857                | Springs, shock (natural finish) (GTX) (1.450 rate) (2)  |
| 7858                | Springs, shock (natural finish) (GTX) (1.538 rate) (2)  |
|                     | Spur Gears & Pinion Gears   |
| 6484X               | Gear, 11-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw  |
| 6485X               | (compatible with steel spur gears)<br>Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw                    |
| 04007               | (compatible with steel spur gears)  |
| 6486X               | Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw  |
| 6488X               | (compatible with steel spur gears)<br>Gear, 14-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw                    |
| • • • • • • •       | (compatible with steel spur gears)  |
| 6487X               | Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw  |
| 6489X               | (compatible with steel spur gears)<br>Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw                    |
| • • • • • • •       | (compatible with steel spur gears)  |
| 6490X               | Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw  |
| 6491X               | (compatible with steel spur gears)<br>Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw                    |
|                     | (compatible with steel spur gears)  |
| 6494X               | Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)                       |
| 6495X               | Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw  |
|                     | (compatible with steel spur gears)  |
| 6496X               | Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw  |
| 6447X               | (compatible with steel spur gears)<br>Spur gear, 46-tooth, steel (1.0 metric pitch)                                       |
| 6448X               | Spur gear, 50-tooth, steel (1.0 metric pitch)   |
| 6449X               | Spur gear, 54-tooth, steel (1.0 metric pitch)   |
|                     | Steering Components   |
| 5119                | Ball bearings, blue rubber sealed (10x15x4mm) (2)   |
| 5116<br>7747        | Ball bearings, blue rubber sealed (5x11x4mm) (2)<br>Servo horn, steering/ linkage, steering (46mm, assembled with pivot   |
|                     | balls)  |
| 7746                | Steering bellcranks/ bellcrank support/servo saver/ servo saver   |
| 7746X               | spring/ draglink/ 3x20mm shoulder screws (2)<br>Steering link, steel/ servo saver spring, heavy duty (use with            |
|                     | #2085X metal gear servo)  |
| 7748                | Toe links, molded composite, 173mm (158mm center to center)   |
| 7748X               | (black) (2)<br>Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,   |
|                     | stronger than titanium) (157mm) (2)/ rod ends, assembled with   |
| 7748G               | steel hollow balls (4)/ aluminum wrench, 10mm (1)<br>Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum,          |
| 11400               | stronger than titanium) (157mm) (2)/ rod ends, assembled with   |
|                     | steel hollow balls (4)/ aluminum wrench, 10mm (1)   |
| 7748R               | Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with   |
|                     | steel hollow balls (4)/ aluminum wrench, 10mm (1)   |
|                     | Suspension Linkage  |
| 7798                | Insert, threaded steel (replacement inserts for #7748X TUBES)   |
| 7707                | (includes (1) left and (1) right threaded insert)   |
| <b>7797</b><br>7743 | Rod ends (4) (assembled with steel pivot balls)<br>Suspension pin retainer (4)  |
| 7740                | Suspension pin set, front or rear corner (hardened steel), 4x85mm   |
| 7740                | (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)  |
| 7742                | Suspension pin set, shock mount (front or rear, hardened steel),<br>4x25mm (2), 4x38mm (2)                                |
| 7741                | Suspension pins, 4x85mm (hardened steel) (2)  |
| 7748                | Toe links, molded composite, 173mm (158mm center to center)   |
| 7748X               | (black) (2)<br>Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,   |
|                     | stronger than titanium) (157mm) (2)/ rod ends, assembled with   |
| 77490               | steel hollow balls (4)/ aluminum wrench, 10mm (1)   |
| 7748G               | Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with |
|                     | steel hollow balls (4)/ aluminum wrench, 10mm (1)   |
| 7748R               | Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with   |
|                     | steel hollow balls (4)/ aluminum wrench, 10mm (1)   |
|                     | Team Traxxas Items  |
| 2514                | Decal sheet, racing sponsors  |
| 9950                | Official Team Traxxas® racing decal set (flag logo/ 6-color)  |
| 9909                | Traxxas® racing banner, red & black (3x7 feet)  |
|                     | Tires & Wheels  |
| 7772A               | Tires & wheels, assembled, glued (X-Maxx® black chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2)           |
|                     | WIGGIS, MAANU AT LIES, IVAILI HISTILSI (ITIL & HUILI (2)  |

Trizza intesta wheels, assembled, glued (X-Maxx® black cholme wheels, Maxx® AT tires, foam inserts) (left & right) (2)
 Trizza intesta wheels, assembled, glued (X-Maxx® black wheels, Maxx® AT tires, foam inserts) (left & right) (2)

|   | -             | -  |
|---|---------------|--|
|   | 7773          | Tires & wheels, assembled, glued (X-Maxx® black wheels,<br>paddle tires, foam inserts) (left & right) (2)        |
| 1 | 7772G         | Tires & wheels, assembled, glued (X-Maxx® green wheels,<br>Maxx® AT tires, foam inserts) (left & right) (2)      |
|   | 7772T         | Tires & wheels, assembled, glued (X-Maxx® orange wheels,<br>Maxx® AT tires, foam inserts) (left & right) (2)     |
|   | 7772R         | Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2)  |
|   | 7770X         | Tires, Maxx® AT (left & right) (2)/ foam inserts (2)   |
|   | 7757          | Wheel hex clips (6)  |
|   | 7756          | Wheel hubs, hex (2)/ hex clips (2)   |
|   | 7756X         | Wheel hubs, hex, aluminum (blue-anodized) (4)  |
|   | 7756G         | Wheel hubs, hex, aluminum (green-anodized) (4)   |
|   | 7756R         | Wheel hubs, hex, aluminum (red-anodized) (4)   |
|   | 7758A         | Wheel nuts, splined, 17mm, serrated (black-anodized) (4)   |
|   | 7758          | Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)  |
|   | 7758G         | Wheel nuts, splined, 17mm, serrated (green-anodized) (4)   |
|   | 7758R         | Wheel nuts, splined, 17mm, serrated (red-anodized) (4)   |
|   | 7771          | Wheels, X-Maxx®, black (left & right)  |
|   |               | Transmission Components  |
|   | 7796          | Center drive, torque-biasing (assembled)/ 17x26x5 ball bearings (2)  |
|   | 1190          | (requires #7727X bulkheads)  |
|   | 7787          | Covers, gear (3)   |
|   | 7785X         | Input gear, transmission, 20-tooth/ 2.5x12mm pin   |
|   | 7786X         | Input shaft, transmission (cush drive)   |
|   | 5040          | Oil, differential (20M weight) (standard)  |
|   | 7784X         | Output gear, 51-tooth, metal (requires #7785X input gear)  |
|   |               | Traxxas Tools  |
| 1 | 3433X         |  |
|   | 3433A<br>3433 | Body reamer (aluminum handle)<br>Body reamer (plastic handle)  |
|   | 3436          | Cap, body reamer   |
|   | 3432          | Scissors, curved tip   |
|   | 3431          | Scissors, straight tip   |
|   | 3415          | Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,  |
|   | ••••          | 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut   |
|   |               | drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips,   |
|   |               | #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/   |
|   |               | driver handle  |
|   |               | Turnbuckles & Threaded Rods  |
|   | 7798          | Insert, threaded steel (replacement inserts for #7748X TUBES)  |
|   |               | (includes (1) left and (1) right threaded insert)  |
|   | 7797          | Rod ends (4) (assembled with steel pivot balls)  |
|   | 7748          | Toe links, molded composite, 173mm (158mm center to center)  |
|   |               | (black) (2)  |
|   | 7748X         | Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,   |
|   |               | stronger than titanium) (157mm) (2)/ rod ends, assembled with  |
|   | 7748G         | steel hollow balls (4)/ aluminum wrench, 10mm (1)<br>Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, |
|   | 7740G         | stronger than titanium) (157mm) (2)/ rod ends, assembled with  |
|   |               | steel hollow balls (4)/ aluminum wrench, 10mm (1)  |
|   | 7748R         | Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum,  |
|   |               | stronger than titanium) (157mm) (2)/ rod ends, assembled with  |
|   |               | steel hollow balls (4)/ aluminum wrench, 10mm (1)  |
|   |               |  |
|   |               |  |
|   |               |  |

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS (1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com TRAXXAS.COM